


PRODUCT INFORMATION & INSTALLATION GUIDE 2026

Airius Model 400/PS-4

ONYX SERIES

EX-ONYX-400-P4-STD-230-WABS

www.airius.co.uk

AIRIUS®
saving you energy

MODEL 400/PS-4 DIMENSIONS AND PROPERTIES



Free hanging units can be angled up to 90° off vertical

UNIT SIZE	STANDARD
Weight:	13.2 kgs *(29 lbs)*
Height to Rim:	476 mm *(18.8 in)*
Total Height:	658 mm *(25.9 in)*
Diameter:	524 mm *(20.7 in)*
MOTOR	**230V @ 50 Hz**
Watts*:	193
RPM*:	1400
L/S*:	964 *(2043 CFM)*
m^3/hr:	3471
AMPS*:	0.85

*Motor data provided by motor manufacturer and is subject to change at anytime
[1]Velocity profile tested in situ

COVERAGE

	Heating	Cooling
Ceiling Height =	Up to 20 m *(65 ft)*	Up to 14 m *(45 ft)*
Nozzle Height =	Up to 19 m *(62 ft)*	Up to 13 m *(42 ft)*
Floor Area =	Up to 232 m^2 *(2500 ft^2)*	Up to 140 m^2 *(1506 ft^2)*

All data is indicative only and can change subject to application. For more accurate design please contact Airius.

NOISE LEVELS

Sound Pressure Level = 46.3 dB(A)

Calculated from nozzle of unit to head height when installed at maximum ceiling height

For additional noise level information contact Airius

MOTOR

Single Phase

PSC - Permanent Split Capacitor motor

230 Volt @ 50 Hz

COLOUR

Cool gray 2C - Off white as standard

Can be tailor painted to your colour specifications

Titan Series Upgrade - Off white as standard

OPERATING TEMPERATURES

Operating Temperature = -25°C (-13°F) to 70°C (158°F)
Thermal Cut Off = 70°C (158°F)

ACCESSORIES & OPTIONS

Optional speed controls allow for variable output from Airius unit.

1 AMP and 5 AMP controls available

For horizontal installations Airius recommend the use of a cradle, a second cable or a rod attachment to support the fan nozzle

HOUSING

PC/ABS Resin - Inc. internal fixed blade stator, nozzle and cowl

UL 94 5VA flame resistance rating

1.8 m steel safety leash cable (fastened to housing)

Applicable to Titan Series Upgrade - Chemical resistant ABS resin housing and stator blades with stainless steel fixings

INGRESS PROTECTION

IP44 Rated

WARRANTY

3 years parts and workmanship from shipping date
120 day money back guarantee (T's & C's apply)

UNIT PLACEMENT

PREPARATION

Install electrical circuit(s) and outlet(s) in accordance with national and local electric codes.

Outlets should generally be mounted vertically unless a “twist/locking” type is being used.

Wall switch may be installed in circuit to disable power and prevent electrical hazards when servicing.

Confirm electrical continuity of Airius unit on the ground before permanently mounting in the ceiling.

MAINTENANCE

Frequency of cleaning will vary by application and environment.

You may clean the plastic housing with a damp warm cloth, using mild household detergents.

Do not use petroleum products, thinners or solvents to clean any part of the Airius unit.

If the Airius unit fails, contact manufacturer.

MATERIALS & PROPERTIES

Constructed from recyclable materials.

The outer shell, stator and fan blades are fire rated UL 94 5VA materials.

Power cord is a 1.8 m, 3 wire, 1.02 mm diameter 300VAC rated electrical cord - CE/EU compliance rated as HO5VV (PLUG NOT SUPPLIED).

Single phase, shaded pole, single speed, axial motor.

Motor is thermally protected. Cut off is at 70°C.

No lubrication required. Bearings are sealed.

OPERATION

Designed to operate 24 hours-a-day, 7 days-a-week to maintain air circulation/thermal equalization/humidity equalization.

Use optional speed control to fine tune RPM if needed.

INSTALLATION

Do not hard connect fans in excess of 10 kgs unless agreed with Airius prior to Installation. When attaching it is preferred if some chain or cable is used between fan and the support. However it is not imperative.

Hang from the ceiling, typically 300 mm (12”) - 450 mm (18”) from the roof deck to fan intake.

For cooling applications fans can be installed slightly lower. Contact Airius for design details and assistance.

The Airius unit performs best when air column from the nozzle is unimpeded to the floor.

The Airius unit should not be mounted directly in front of heat ducts, vents or any other high heat source.

Use professionally installed hardware, capable of supporting a minimum of five times the weight of the fan unit.


Hardware to hang the unit includes but is not restricted to: Hooks, chains, cables, carabiners, bridle rings, beam clamps and bolts.

Density of the placement is directly related to the effectiveness, performance and savings.


Mount out of reach from people and animals.

Floor plans, mezzanines, office locations, machinery, people placement, plumbing, lighting, duct work, electrical systems, natural light/air systems, cranes, doors, windows, ventilation and fire suppression systems are all factors in properly locating the Airius system within the ceiling.

CHAIN HUNG (STRAIGHT)



CHAIN HUNG (ANGLED)





AIRIUS®
saving you energy

Airius Europe, Middle East & Asia

Airius Europe Ltd
Holwell Farm, Cranborne
Dorset
BH21 5QP, UK
Tel - +44 (0) 1202 554200
Email - info@airius.co.uk
Web - www.airius.co.uk

Airius Americas

Email - Info@airiusfans.com
Web - www.airiusfans.com

Airius Oceania & S.E. Asia

Email - info@airius.com.au
Web - www.airius.com.au

USA and foreign Patents granted to AIRIUS LLC, USA, further patents pending. AIRIUS & AIRIUS SYSTEMS is the copyright property of AIRIUS LLC, USA. All material issued by, or emanating from, Airius Europe Ltd is the Copyright property of Airius Europe Ltd, UK.

V 1.0